

Flush Mounted Compact LED Light - FMCLED Series

Function


Flush mounted compact LED Lights are suitable for water features, jacuzzi and swimming pools. The LED illumination comes with options of warm white, cool white or RGBW LED lighting. The stainless steel fixture is corrosion resistant. Its mirror finish and compact size make it suitable to be used in small and shallow water features. Available in white LED as on/off control for non-sequencing fountains or as optional DMX control or DALI control for sequenced fountains.

The stainless steel niche provides flush mounted installation with pool wall, Interior space for the length of cable to be coiled in order to allow for future maintenance of light without having to drain the pool.



Specifications

Power 5W - 8W	Beam Angle: 45° as standard/ Optional 15° lens (custom lens available upon request)	Standard Cable Length 1.5 m (H07RN-F) (Custom length available on request)
Operating Voltage 24V DC	Dimmable: DMX control DALI control	Material: Stainless steel 316
Min. - Max Voltage 18V DC - 30V DC	Reverse polarity protection: Yes	Front Cover: Polycarbonate clear cover with UV Protection
Operating mode: Constant Current	Transient spike protection: Yes	Protection Rating: IP 68, IK 10
Colours RGBW / White	High temperature protection: Yes	
No. of LED 1	EMC complaint: Yes	
RGBW LED type 4 in 1 Cree LED	Cable 4 C - 1 mm ² (DMX light) 2 C - 1.5 mm ² (White light)	




Model No.	Description	Material	Colour	Control	Power (W)	Luminous flux (lm)	A (mm)	B (mm)	C (mm)	D (mm)
FMCLED-S006	RGBW Flush Mounted Compact LED Light	Stainless steel 316	RGBW	DMX	8	126	129	158	100	7
FMCLED-S010	Cool white Flush Mounted Compact LED Light	Stainless steel 316	Cool white	On/off	5	291	129	158	100	7
FMCLED-S011	Warm white Flush Mounted Compact LED Light	Stainless steel 316	Warm white	On/off	5	228	129	158	100	7


* Add suffix DMX to model number to order DMX controlled white light. i.e. FMCLED-S011-DMX

* Add suffix DALI to model number to order DALI controlled white light. i.e. FMCLED-S011-DALI

* Add suffix AUTO to model number to order Auto colour changing effect for RGBW light. i.e. FMCLED-S006-AUTO

Flush Mounted Compact LED Light	FMCLED Series	Model No. FMCLED	Rev. 4	
The information contained in this drawing is the sole property of Aquashi. Any reproduction in part or as a whole without the written permission of Aquashi is prohibited. Aquashi reserves the right to update all designs, specifications and data sheets without prior notice.				

Flush Mounted Compact LED Light - FMCLED Series



F Photometric Polar diagram: (RGBW)

FMCLED-010 - Cool White

Colour Rendering Index [CRI] - 76.9

Correlated Colour Temperature (K) [CCT] - 5200

FMCLED-011 - Warm White


Colour Rendering Index [CRI] - 87.3

Correlated Colour Temperature (K) [CCT] - 3086

*IES files available on request.


Connection Diagram

RGBW Light Cable





** DALI cable Connection on request.

Warm White/ Cool White Light Cable



Typical Installation



Flush Mounted Compact LED Light	FMCLED Series	Model No. FMCLED	Rev. 4	
The information contained in this drawing is the sole property of Aquashi. Any reproduction in part or as a whole without the written permission of Aquashi is prohibited. Aquashi reserves the right to update all designs, specifications and data sheets without prior notice.				