

# Free Standing LED Light - FSLED Series

## Function

The free standing underwater LED lights can be used with a variety of fountain nozzles to give spectacular colours to water with its white or RGBW colour changing technology. Ideal for sequenced fountains as the DMX controllability provides additional control for choreographed sequencing effects and virtual effects with water. Available in white LED as on/off control for non-sequencing fountains or as optional DMX control for sequenced fountains. Auto colour changing available for DMX controlled RGBW lights. DMX controlled white lights are dimmable as well as sequencing. Optional rock guard is available on request.

## Specifications

**Power**

30W - 35W

**Operating Voltage**

12-24V DC

**Min. - Max Voltage**

11V DC - 30V DC

**Operating mode:**

Constant Current

**Colours**

RGBW / White

**No. of LED**

6 (RGBW)

9 (white)

**Beam Angle:**

30 ° as standard / Optional 15 & 45 ° lens (custom lens available upon request)

**RGBW LED type**

4 in 1 Cree LED

**Dimmable:**

DMX control

(0-10V DC available upon request)

**Reverse polarity protection:** Yes

**Transient spike protection:** Yes

**High temperature protection:** Yes

**EMC complaint:** Yes

**Cable**

4 C - 1 mm<sup>2</sup> (DMX light)

2 C - 1.5 mm<sup>2</sup> (White light)

**Standard Cable Length**

2 m (Custom length available on request)

**Material:**

Light Fixture: Brass / Stainless steel 316

Light Stand: Brass and Stainless steel 316

**Front Cover:**

Polycarbonate clear cover with UV Protection (Optional SS316 rock guard)


**Protection Rating:** IP 68, IK 10

**Height with stand:**

Min. Height: 295mm

Max. Height: 405mm

(Custom Height available on request)



Model No.	Description	Material	Colour	Control	Power (W)	Luminous flux (lm)	A (mm)	B (mm)	C (mm)
FSLED-S035	Stainless RGBW Free standing LED light	Stainless steel 316	RGBW	DMX	35	1422	169	56	38
FSLED-B035	Brass RGBW Free standing LED light	Brass	RGBW	DMX	35	1422	169	56	38
FSLED-S031	Stainless Cool white Free standing LED light	Stainless steel 316	Cool white	On/off	30	2146	169	56	38
FSLED-B031	Brass Cool white Free standing LED light	Brass	Cool white	On/off	30	2146	169	56	38
FSLED-S032	Stainless Warm white Free standing LED light	Stainless steel 316	Warm white	On/off	30	1782	169	56	38
FSLED-B032	Brass Warm white Free standing LED light	Brass	Warm white	On/off	30	1782	169	56	38


\* Add suffix DMX to model number to order DMX controlled white light. i.e. FSLED-S032-DMX

\* Add suffix RG to model number to order optional rock guard. i.e. FSLED-S035-RG

\* Add suffix AUTO to model number to order Auto colour changing effect for RGBW light. i.e. FSLED-S035-AUTO

Free Standing LED Light	FSLED Series	Model No. FSLED	Rev. 2	
<p>The information contained in this drawing is the sole property of Aquashi. Any reproduction in part or as a whole without the written permission of Aquashi is prohibited. Aquashi reserves the right to update all designs, specifications and data sheets without prior notice.</p>				

# Free Standing LED Light - FSLED Series



F Photometric Polar diagram: (RGBW)

**FSLED-031 - Cool White**

Colour Rendering Index [ CRI ] - 80.3  
 Correlated Colour Temperature (K) [ CCT ] - 5700


**FSLED-032 - Warm White**

Colour Rendering Index [ CRI ] - 85.3  
 Correlated Colour Temperature (K) [ CCT ] - 3000


\*IES files available on request.

## Connection Diagram


**RGBW Light Cable**




**Warm White/ Cool White Light Cable**



## General Dimensions



Free Standing LED Light	FSLED Series	Model No. FSLED	Rev. 2	
The information contained in this drawing is the sole property of Aquashi. Any reproduction in part or as a whole without the written permission of Aquashi is prohibited. Aquashi reserves the right to update all designs, specifications and data sheets without prior notice.				