Underwater LED Swimming Pool Light - LSP-DVS Series

Function

Niche mounted DVS Series LED lamps has a strong level of lumen output which strongly lit concrete pools. Available in white or colour changing LED. The lights consists of a stainless steel 316 face plate with an ABS or Stainless steel 316 niche. The LED lamp is fully sealed so water cannot penetrate or damage the fixture. Fitted with the Quick Connect cabling system that is reliable and easy to mount.

RGB LED lights have an embedded 16 programmed animation can be controlled using the RF remote (RM-200) or by simply turning off and on the lamps in a sequenced manner.



Specifications

Power 32W - 40W **Voltage** 12V AC


Colours RGB / Day White

Beam Angle: 116 ° Control On/off Cable 2 C - 1 mm² Standard Cable Length 2 meters Temperature range:


+40° water temperature

Lamp Life: 25,000 Hrs Protection Rating: IP 68

IP 68 IEC class III



Model No.	Description	Niche type	Colour	Power (W)	Luminous flux (Im)	A (mm)	B (mm)	C (mm)	D (mm)	E (BSP) Female thread
LSP-DVS-170RGB-ABS	ABS niched RGB LED Swimming Pool light	ABS	RGB	32	2450	272	216	137	125	3/4"
LSP-DVS-170WH-ABS	ABS niched Day white LED Swimming Pool light	ABS	Day white (5000 K)	40	3950	272	216	137	125	3/4"



Model No.	Description	Niche type	Colour	Power (W)	Luminous flux (Im)	A (mm)	B (mm)	C (mm)	D (mm)	E (BSP) Female thread
LSP-DVS-170RGB-SS	SS 316 niched RGB LED Swimming Pool light	SS316	RGB	32	2450	272	225	125	70	3/4"
LSP-DVS-170WH-SS	SS 316 niched Cool white LED Swimming Pool light	SS316	Day white (5000 K)	40	3950	272	225	125	70	3/4"

Underwater LED Swimming Pool Light	LSP-DVS Series	Model No. LSP-DVS	Rev. 0	
The information contained in this d without the written permission of Aq and data sheets without prior notice	aquashi			

Underwater LED Swimming Pool Light - LSP-DVS Series




Precautions:

* LSP-DVS series lamps must be completely submerged into water during operation.

* For operation only with safety isolation transformer

Connection Diagram



Typical Installation

